

PILOT MESSAGES

Axios Products, Inc
353 Veterans Highway, Suite 204
Commack, NY 11725
Sales/Administration: (800) 877-0990 info@axiosproducts.com
Technical Support: (631) 864-3666 support@axiosproducts.com
Telecopier (Fax): (631) 864-3693 www.axios.com

Preface

This publication contains information necessary for the operation of PILOT, a family of proprietary program products used for performance management and capacity planning. It provides data processing managers, system programmers, and capacity planners with information required to use this product.

Information in this publication is subject to significant change.

THIS MANUAL IS PROVIDED FOR THE SOLE AND EXCLUSIVE USE OF THE CUSTOMER. THE MATERIAL CONTAINED IN THIS MANUAL IS CONFIDENTIAL AND SHOULD BE SO TREATED. COPIES MAY BE PURCHASED FROM AXIOS PRODUCTS, INC. ANY UNAUTHORIZED REPRODUCTION OF THIS MANUAL IS PROHIBITED.

Seventh Edition (November, 2007)

This edition applies to Version 1.7 of the PILOT program products and to all subsequent versions and modifications until otherwise indicated in new editions or newsletters.

© Copyright 1987-2007 Axios Products, Inc. All rights reserved.

Contents

Message Formats..	1
Information Messages..	3
Warning Messages..	7
Error Messages..	9
User Abends.	21
Table Error Return Codes.	22
Index	23

Message Formats

All PILOT messages have a message number in the following format:

PILOTxxxI
PILOTxxxW
PILOTxxxE

where:

xxx
is a unique message number.

I
indicates that the message is informational. The message numbers will be in the range of 001 to 099.

W
is used for warning messages pointing out possible errors or omissions and the default action taken by PILOT. These messages are numbered 100-199.

E
is used for error messages. The message text will indicate the problem which is preventing PILOT from continuing. The message numbers will be in the 200-999 range.

Miscellaneous messages and User Abends

Miscellaneous unnumbered messages and User Abends are included at the end of this section of the manual.

Information Messages

PILOT001I

SEVERE ERROR NO RECORDS EXTRACTED*****

A serious error has occurred and the run is terminated. A syntax or logic error was detected. The statistics log will contain additional messages to point to the problem. Correct the cause of the error and resubmit the job.

PILOT002I

CHECK REQUESTED TIME FRAME ON CONTROL CARD

The time range specified on the control card was not found in the input data set. A completion code of 8 is given at step termination.

PILOT003I

CHECK SYSUT1, DATA SET MAY NOT CONTAIN THE DATA SPECIFIED

The criteria specified in the control cards were not met with the input data set. Optional key word such as system, account, etc. should be checked. Also refer to message PILOT002I.

PILOT004I

******READSMF EXIT ACTIVE
MODULE=XXXXXXX,
PARMS=YYYYYYYY/NONE**

The exit is given control with the parameters (if any) to process each record extracted. Program READSMF passes each record to the active exit.

PILOT005I

READSMF DEFAULT VALUES USED

This indicates that SYSIN DD was dummied. All records will be processed.

PILOT006I

SORT IS ACTIVE FOR NODUP

Program READSMF invoked SORT to detect and delete duplicate records.

PILOT007I

ISMF OPTION ACTIVE. LINK TO IFASMFDP WAS SUCCESSFUL

Program READSMF invoked program IFASMFDP to clear the system SMF data set after it was successfully copied.

PILOT008I**ESTAE MACRO FAILED NO ERROR
RECOVERY ESTABLISHED**

Recovery for system 002 abends can not be provided. Processing continues. This message is issued if program READSMF does not have sufficient virtual shortage. If an 002 abend occurs, increase the region size.

PILOT009I**THE DATA SET IS ALREADY OPEN,
AND WILL NOT BE FORMATTED**

The system SMF data set was opened by another job. Processing continues but IFASMFDP will not be called to clear the data set. Another job may be using the active data set. The dump is complete, but the data set is not cleared. Either another job is running to clear the data set or a OS command was not issued to switch the active SMF data set. If this last case is true, use the sample IEFU29 exit and review the installation procedures for this function.

PILOT010I**PILOT010I READY TO RESET
DSN=SYS1.MANx
*nn PILOT010I REPLY YES TO
RESET THE DATA SET RBA TO 0 OR
REPLY NO**

This two line message indicates that the system SMF data set was processed by program READSMF and is ready to be cleared. Processing continues. IFASMFDP will be called to clear the data

set if "YES" is replied. A reply of YES will clear the data set, a reply of "NO" will not clear the data set.

PILOT011I**CCYYDDD.HH.MM MVS=mmm,
SU/SEC=sssss,IPS=pp,ICS=ii,HIGH
PGN=xxxx**

This message describes the input file RMF Type 72 record, where: mmm is the MVS release; sssss is the SRM constant found on the record; pp and ii are the suffixes for the IPS and ICS from which the record was built; and xxxx is the highest performance group defined for this record.

PILOT012I**PARMLIB SUBSYSTEM=sssssss,
TRXNAME=ttttttt,CTL=cccc,
RPT=rrrr**

This message shows the definition of a report performance group in the ICS.

PILOT013I**PARMLIB OPENED FOR MEMBER=
mmmmmmmm IEAICSc**

Displays the member in SYS1.PARMLIB processed to define report performance groups.

PILOT014I

*****SYSUT2 LRECL=32756,
RECFM=VBS, DFP DEFAULT
BLOCKSIZE USED**

DFP release 3.1 and above will automatically use a half track blocking factor when DCB parameter BLKSIZE=0 is specified. If no DCB parameters are specified for SYSUT2, this default will be used.

**PILOT INFORMATION MESSAGES
FOR THE CONVHIST PROGRAM**

PILOT015I

**PILOT 1.7 History Conversion Program
- Copyright Axios Inc. 1999.**

The CONVHIST program issues this initial copyright message prior to processing the history files.

PILOT016I

**HISTORY CONVERSION HAS
COMPLETED. HIGHEST RETURN
CODE = XXXX.**

This message indicates the CONVHIST program has completed converting the history file, and received the return code indicated as the highest exception response to any of its internal processing.

PILOT017I

**CLOSING HISTORY INPUT FILE
FOR QSAM ACCESS.**

The CONVHIST program has completed its first pass of the history file's directory information. This phase obtains all of the member names that will be processed in the conversion.

PILOT018I

**FOUND HISTORY MEMBER NAME:
XXXXXXXXXX**

This message states the indicated member name was found during the initial directory scan of the input history file, and will be included in the conversion process.

PILOT019I

**NUMBER OF DIRECTORY
BLKS=XXXXXX, AND NUMBER OF
MEMBERS=XXXXXX.**

This message reflects the total number of directory blocks and members encountered in the initial scan of the input history file's directory.

PILOT021I

**LOADING DIRECTORY FOR
MEMBER: XXXXXXXXX**

During the second phase, CONVHIST obtains enough storage to save information about each history member, and then proceeds to load that directory information into the storage. This message

indicates the member being processed during this second phase.

PILOT022I

**LOADED DIRECTORY
BLKS=XXXXXX FOR XXXXXX
MEMBERS.**

CONVHIST has completed the second phase, and has loaded directory information from the indicated number of directory blocks and members.

PILOT023I

**CONVERTED INPUT MEMBER
XXXXXXXXX TO OUTPUT MEMBER
XXXXXXXXX.**

The CONVHIST program is in the third phase, and has converted the indicated member from the shown input member name to the displayed output member name. Notice the member names are different.

PILOT024I

**CONVERTING MEMBER:
XXXXXXXXX**

The CONVHIST program is in the third phase, and indicates the input history member it is currently processing in this message.

PILOT025I

**HISTORY MEMBERS CONVERTED
= XXXXXX.**

The CONVHIST program has completed the third phase, and indicates the number of members it has converted.

Warning Messages

PILOT101W

*****SYSUT2 DCB PARAMETERS FORCED IDENTICAL TO SYSUT1**

DCB parameters were not specified for SYSUT2 with DISP=NEW. Program READSMF copies the DCB parameters from SYSUT1 to SYSUT2 and continues processing. A completion code of 4 is given at step termination. If the input file was a tape and the output file is a disk, an abend S002 may occur (refer to the performance section of the PILOT/SMF manual).

PILOT102W

NON-SWAP REQUEST WAS IGNORED

Program READSMF was not generated with AUTH=Y at installation time. Processing continues. READSMF will not request that its address space become non-swappable. If performance is a major factor, discuss this option with the system programmer at your installation.

PILOT103W

ISMF OPTION ACTIVE. LINK TO IFASMFDP WAS UNSUCCESSFUL

The system SMF data set was backed up but a problem occurred when the data set was cleared. Processing continues.

READSMF will not clear the system data set. The backup of the data set is valid. Contact the systems programmer at your installation. Dynamic allocation may have failed for the control card that is built and passed to IFASMFDP or the module IFASMFDP can not be loaded.

PILOT104W

UNABLE TO GET STATISTICS FOR FILE xxxxxxxx

Program READSMF could not obtain I/O counts for either an input or output file. Processing continues. This will occur if a RDJFCB macro fails after files are processed. The data collected is good, but effects the dynamic input feature of PILOT/SMF. Contact Axios technical support for a further explanation of this condition.

PILOT105W

LRECL OF RECORD GREATER THAN 240, TITLES WILL BE OMITTED

The maximum length of a record for processing by Lotus 1-2-3 is 240 bytes. This error occurs when program SMFPC has too many channel paths specified or none are specified and program SMFPC attempts to format all channel paths.

PILOT106W

**** ERROR ** MORE THAN 4 PERIODS IN A PERFORMANCE GROUP FOR TSO**

Program SMFPC can only process 4 periods for a TSO performance group. Additional periods are ignored.

PILOT107W

**** WARNING PERFORMANCE GROUP DEFINITION CHANGED DURING PROCESSING**

The number of performance groups found during processing was increased from the first definition read. An additional entry is made in our tables to accommodate the new performance group. This is usually caused by a different IPS being used. This may not be an error if the other performance groups were not changed. The data may need to be analyzed separately.

PILOT108W

PGN=nnn NOT FOUND IN RECORDS PROCESSED

A user-defined workload specified a performance group that was not found on the input file.

PILOT109W

RPGN=xxxx FOUND IN ICS BUT NOT IN CURRENT IPS. HIGHEST PGN=yyyy

The report performance group defined in the ICS specified was not found on the current RMF 72 record. The IPS/ICS may have changed in the input file.

PILOT110W

CPU INTERVAL RECORD MISSING, OVERHEAD CALCULATIONS MAY BE INVALID

RMF type 70 records are required as input to calculate the un-captured MVS overhead.

PILOT111W

PERFORMANCE GROUP NOT FOUND FOR WORKLOAD

A user-defined workload performance group was not found. It may not exist in the input file.

PILOT112W

RPGN=nnnn FOR SUBSYS=sssssss WIL NOT BE PROCESSED

A user-defined workload report performance group will not be processed because it cannot be found in the IPS.

Error Messages

PILOT201E

****ERROR** KEYWORD 'XXXX'
MISSING*******

The specified keyword is required for program READSMF processing (SELECT, START, and END). The run is terminated with a completion code of 16. No input records are processed.

PILOT202E

****ERROR** START/END KEYWORD
INCORRECTLY SPECIFIED**

A syntax error of some type (not enough digits, no digits, etc.). The run is terminated with a completion code of 16. No input records are processed.

PILOT203E

****ERROR** DATE SEQUENCE
ILLOGICAL**

The date on the END keyword is earlier than the date on the START keyword. The run is terminated with a completion code of 16. No input records are processed.

PILOT204E

****ERROR** SELECT KEYWORD IN-
CORRECTLY SPECIFIED**

A syntax error of some type. Parenthesis must be used for multiple selections. Only numbers are valid input. The run is terminated with a completion code of 16. No input records are processed.

PILOT205E

****ERROR** ACCOUNT KEYWORD
INCORRECTLY SPECIFIED**

A syntax error of some type. Too many alphanumeric characters, a parenthesis is not used, etc. The run is terminated with a completion code of 16. No input records are processed.

PILOT206E

****ERROR** xxxxxxxxx IS AN INVAL-
ID KEYWORD**

The above text is not acceptable to program READSMF. This could be a keyword incorrectly spelled or specified. A missing comma or parenthesis could cause a valid keyword to become invalid. The last case would cause another message to be issued. The run is terminated with a completion code of 16. No input records are processed. If no other messages are

issued the cause may be a comment incorrectly specified.

PILOT207E

****ERROR** ONLY TYPES 70 - 79 ARE VALID WITH TIME=M (RMF RECORDS)**

The TIME=M parameter was specified. This parameter is only valid when processing RMF records. Only types 70-79 are valid. The run is terminated with a completion code of 16. No input records are processed.

PILOT208E

****ERROR** CONTROL CARD ENDED WITH A COMMA EXPECTED CONTINUATION**

Another control card was expected, but none was found. The run is terminated with a completion code of 16. No input records are processed. If no other messages are issued the cause may be a comment specified incorrectly.

PILOT209E

****** NO RECORDS FOUND IN SPECIFIED RANGE ******

Program READSMF did not find records that fall between the START= and END= parameters. Processing continues. READSMF will give the date range found on the input file. A return code of 8 is given.

PILOT210E

HISTORY OPTION MUST BE ACTIVE WITH ISMF OPTION

Program READSMF will not dump and clear a system SMF data set without the presence of an audit data set. The step is terminated with a return code of 16. No input records are processed.

PILOT211E

****ERROR** SYSTEM KEYWORD INCORRECTLY SPECIFIED**

The SYSTEM= keyword is in error. This message will be issued if it is specified more than once or too many characters are specified. The run is terminated with a completion code of 16. No input records are processed.

PILOT212E

**** XX RETURN CODE FROM SORT
** CHECK SORT MESSAGES****

SORT failed when the NODUP option was chosen. Most likely causes are insufficient storage or work space, or a missing DD statement. The run is terminated with a completion code of 16. No other processing is done.

PILOT213E

****ERROR** XXXXXXXX KEYWORD INCORRECTLY SPECIFIED**

A syntax error of some type. For multiple values the required parenthesis were not

used, etc. The run is terminated with a completion code of 16. No input records are processed.

PILOT214E

****ERROR** MORE THAN 50 JOB ENTRIES SPECIFIED IN JOBNAME KEYWORD**

The capacity of READSMF's internal table of job names or masks has been exceeded. The run is terminated with a completion code of 16. No input records are processed. Use the mask feature of the JOBNAME keyword to specify fewer than 50 entries.

PILOT215E

Reserved.

PILOT216E

MODULE XXXXXXXXX NOT FOUND, EXIT IGNORED

A BLDL macro failed to locate the exit specified in the EXEC card PARM field. The run is terminated with a completion code of 16. No input records are processed.

PILOT217E

****ERROR** XXXXXXXX DDCARD MISSING**

The indicated DD card must be included in the JCL job stream. The run is terminated with a completion code of 16.

PILOT218E

****ERROR** PEAKTIME KEYWORD INCORRECTLY SPECIFIED**

The PEAKTIME= keyword is in error. Parenthesis and commas must be used in this keyword. Two time fields are specified for this keyword. The run is terminated with a completion code of 16.

PILOT219E

****ERROR** MORE THAN 16 PERFORMANCE GROUPS SPECIFIED**

More than 16 performance groups were specified for TSO for program SMFPC. The run is terminated with a completion code of 16.

PILOT220E

****ERROR** INVALID PARM SPECIFIED**

A syntax error occurred while processing the parameter field of the EXEC statement. The run is terminated with a completion code of 16.

PILOT221E****ERROR** GETMAIN FAILED FOR TABLE**

There was not enough virtual storage to process the data. The run is terminated with a completion code of 16. Correct this problem by increasing the region size and resubmit the job.

PILOT222E**DYNAMIC ALLOCATION ERROR REASON CODE xxxx ERROR CODE yyyy**

A member in the History file was found that met the specified criteria, but the volume was not available for use. The reason and error codes are returned by the dynamic allocation SVC. An explanation of these values can be found in MVS Systems Programming Library: Job Management. The member is not processed and module RDSMFDYN continues to search the History file.

PILOT223E****ERROR** MORE THAN FOUR PERIODS FOUND IN A PERFORMANCE GROUP**

A TSO performance group is defined with more than four periods for a control performance group in the current record. The record is not processed as a separate period, and is ignored.

PILOT224E**LINK TO IFASMFDP FAILED, REPLY C TO CONTINUE OR U TO ABEND.**

This message indicates that program READSMF could not clear the SMF data set for one of the following reasons:

1. Program READSMF could not Load program RDSMFAUT.
2. Programs READSMF and RDSMFAUT are not authorized.
3. Program IFASMFDP could not be loaded.

When this message is issued, the dump of the SMF data set is valid, but the system data set will not be cleared. If a reply of "U" is given the step will abend. If a reply of "C" is given the step will complete with a condition code of 8. Correct the above problem and resubmit the job, or use IFASMFDP to clear the data set if a reply of "C" was given.

PILOT225E**TERMINATION RETURN CODE PASSED FROM USER EXIT**

An exit loaded by program READSMF encountered an error and requested processing to be terminated. The run is terminated with a condition code 16. Check for additional error messages written by the user exit.

PILOT226E
DYNAMIC ALLOCATION FAILED
FOR SYSUT1

A request to dynamically allocate the input file failed because a suitable member could not be found in the History file. The run is terminated with a condition code 16. Ensure that the date, time, and selection fall within the range of one the members in the History file.

PILOT229E
ACCOUNT POSITION ERROR

While processing a request for extraction by account numbers, program READSMF encountered an error in the record. The record is ignored and processing continues. Ensure that READSMF was generated properly and the account position was specified correctly for your installation. It is possible that a non-IBM SMF record may cause this error. If the product is installed properly, call the Axios technical support group for further assistance.

PILOT230E
DUMPED FAILED FOR
DSN=SYS1.MANx

An I/O error may have occurred and program READSMF and/or IFASMFDP could not process the data set. All records that were written up to this point are good on the output file(s). Contact your systems programmer for additional help. Contact Axios Products technical support group with all the documentation.

PILOT401E
xxxxxxx RMFCTL OPEN FAILED

The control card file could not be opened by the xxxxxxxx routine. The run is terminated with a completion code of 16. Look for additional messages concerning this file in the JES log.

PILOT402E
xxxxxxx INVALID CONTROL CARD

A syntax error was found in the control card file by the xxxxxxxx routine. The run is terminated with a completion code of 16. Look for additional messages concerning this error.

PILOT403E
xxxxxxx DICTIONARY OVERFLOW

An internal error occurred in the routine xxxxxxxx. The buffer was not large enough to handle the control cards. The run is terminated with a completion code of 16. Contact the Axios technical support group.

PILOT404E
xxxxxxx DUPLICATE CARD

A duplicate control card was found by the xxxxxxxx routine. The run is terminated with a completion code of 16. Look for additional messages concerning this error.

PILOT405E**xxxxxxx INVALID CONTINUATION**

A multiple card format of a keyword is in error. Routine xxxxxxxx processed the control card. The run is terminated with a completion code of 16. Look for additional messages concerning this error. Ensure that a comma is followed by a space.

PILOT406E**xxxxxxx CONTROL CARD KEYWORD ERROR**

A syntax error was found. The run is terminated with a completion code of 16. Look for additional messages concerning this error.

PILOT407E**xxxxxxx IS AN INVALID KEYWORD**

An unknown command was found on a card. The run is terminated with a completion code of 16. Look for additional messages concerning this error. Ensure that the keyword does not start in column one and is followed by at least one space.

PILOT408E**xxxxxxx IS A DUPLICATE KEYWORD**

A keyword command was found at least twice. The run is terminated with a completion code of 16. Only the "WKLD"

keyword can be specified more than once. Ensure that the keyword does not start in column one and is followed by at least one space.

PILOT409E**xxxxxxx KEYWORD HAS AN INVALID VALUE**

An unknown value was found on a keyword control statement. The run is terminated with a completion code of 16. Look for additional messages concerning this error. Ensure that the keyword does not start in column one and is followed by at least one space.

PILOT410E**** ERROR ** DDNAME INCORRECTLY SPECIFIED**

The DDNAME= must be specified with up to eight characters for a valid name.

PILOT411E**** ERROR ** GROUP= INCORRECTLY SPECIFIED**

The GROUP= keyword is in error. Parenthesis and commas must be used in this keyword. The run is terminated with a completion code of 16.

PILOT412E**** ERROR ** JOB/ACT INCORRECTLY SPECIFIED**

Program SMFPC30 found a syntax error. Parenthesis and commas must be used in this keyword. Ensure the correct length is used for account numbers and no more than eight characters are used for a job name.

PILOT420E
MORE THAN 400 CARDS IN ICS

A buffer for 400 control cards is used to parse the ICS. Delete any control cards that only have comments if it would bring the total number of input cards below 400.

PILOT421E
XXXXXXXXXX IS AN INVALID OPERAND

An unknown sub-command was found for a keyword. The run is terminated with a completion code of 16. Look for additional messages concerning this error. Ensure that the keyword does not start in column one and is followed by at least one space.

PILOT422E
INVALID VOLSER FOR A DEVICE SPECIFIED

A syntax error occurred for the DEVICE keyword. The run is terminated with a completion code of 16. Ensure that the keyword does not start in column one and is followed by at least one space. If an "*" is used as a mask, ensure that "(" and ")" were used. Volume names are 6 characters or less and must be separated by commas.

PILOT423E
INVALID CPU MODEL SPECIFIED

An unknown CPU model without the SPEED= operand was specified on the CPU control card. The run is terminated with a completion code of 16. See the techniques section of the manual for CPU model names included with PILOT. Correct the problem and resubmit the job.

PILOT424E
INVALID CPU MODEL SPEED SPECIFIED (XXXX.YY)

The SPEED= operand has a syntax error. The run is terminated with a completion code of 16. Ensure that the correct number of digits are specified.

PILOT425E
INVALID CPU MIP SPEED SPECIFIED (XXX.YY)

The MIPS= operand has a syntax error. The run is terminated with a completion code of 16. Ensure the correct number of digits are specified.

PILOT426E
MORE THAN 99 REPORT PGNS FOR ONE CONTROL PERFORMANCE GROUP

A storage limitation of 99 report performance groups is assigned for each control performance group.

This is a warning message for program SMFPC, and processing will continue if possible.

PILOT427E**PARMLIB DDCARD COULD NOT BE OPENED**

ICS parameter was specified and the data set could not be opened.

PILOT431E**MODEL NOT GENERATED DUE TO PREVIOUS ERROR**

Output files created are invalid and additional messages will point to the specific problem.

PILOT428E**PARMLIB MEMBER xxxxxxxx NOT FOUND**

The PARMLIB data set was opened, but member could not be found in the data set allocated by the PARMLIB DD card.

PILOT432E**CPU SPEED CHANGED DURING PROCESSING**

The CPU SRM constant changed during the processing of the input file. This is a fatal error for the model generator program SIMBUILD. Program SMFPC will attempt to continue to process the input file. The current interval may be invalid.

PILOT429E**ERROR PROCESSING ICS**

Ensure that the ICS has valid syntax for the appropriate operating system. If no other message was issued with this error message contact Axios Products, Inc. technical support. Print copies of the ICS and IPS for installation.

PILOT433E**AUTO SPECIFIED FOR SPEED OPERAND ON CPU CONTROL CARD FOR NON-XA**

The SRM constant is not in the RMF records created on non-XA systems. Processing is terminated. The SPEED parameter must be specified.

PILOT430E**PERFORMANCE GROUP DEFINITION CHANGED DURING PROCESSING**

The IPS changed in the time frame of the input file being processed. This error will cause the model generator to terminate.

PILOT450E

**UNKNOWN CONTROLLER TYPE
FOUND, PROCESSING TERMINAT-
ED**

IBM 3880-23 and 3990-03 are the only types of controllers supported using RMF cache reporter records.

PILOT451E

**CONTROLLER TYPE CHANGED, IN-
TERVALS CAN NOT BE COMBINED**

Data can not be combined for a DASD unit because the geometry of the controllers has changed and the statistics will not be meaningful.

PILOT500E

**SMFPC110 MORE THAN 50 TRANS
SPECIFIED**

More than 50 transaction names were specified for an INCLUDE or EXCLUDE operand. The run is terminated with a completion code of 16. Specify transaction names with a mask to reduce the number of table entries then resubmit the job.

PILOT501E

**SMFPC110 TRAN NAME INCORR-
ECTLY SPECIFIED**

The INCLUDE or EXCLUDE operand has a syntax error. The run is terminated with a completion code of 16.

PILOT502E

**SMFPC110 SYNTAX ERROR OC-
CURRED**

The INCLUDE, EXCLUDE, IREG, or EREG operand is incorrectly specified. The run is terminated with a completion code of 16.

PILOT503E

**SMFPC110 GETMAIN FAILED FOR
xxxK**

There is not enough virtual storage to run the program. The run is terminated with a completion code of 16. Increase the amount of storage on the EXEC statement in the JCL and resubmit the job.

PILOT504E

**SYSID - ssss NOT FOUND IN WORK-
LOADS DEFINED**

The input file either contains additional systems that are not to be processed or a mistake was made defining the workload.

PILOT505E

**OVHD RECORD FOUND, SOME
STATISTICS NOT COLLECTED**

Detail records were not collected and full statistics are not available.

PILOT506E

MONITOR FILE NOT VALID FOR INPUT

The input file could not be used as input to the CICS program of PILOT/CICS. Contact Axios Products, Inc technical support if message PILOT507E is also issued.

Check that the data set is not empty, and can be read via ISPF.

PILOT507E**CICS VERSION UNKNOWN, STATISTICS NOT COLLECTED**

The input file into the CICS program was not supported with this release of PILOT/CICS. Contact Axios Products, Inc. technical support.

PILOT508E**INCLUDE/EXCLUDE INCORRECTLY SPECIFIED**

The keyword is in error. Parenthesis and commas must be used in this keyword. The run is terminated with a completion code of 16.

PILOT601E**RDSMFALC DIRECTORY BLOCK COUNT ERROR**

An I/O error occurred while processing the history file directory. The run is terminated with a condition code 16.

PILOT602E**RDSMFALC FIND FAILED FOR MEMBER**

A member was not found in the History library, but there was an entry in the directory. Processing terminates.

PILOT603E**RDSMFDYN PARM LIST INVALID**

A module built an invalid parameter list to dynamically allocate an input file. The run is terminated with a condition code 16. Contact Axios technical support for assistance.

PILOT604E**RDSMFDYN MAX NUMBER OF VOLUMES REACHED**

More than 30 volumes are needed to dynamically allocate an input file. The run is terminated with a condition code 16. Do not use the dynamic allocation feature and resubmit the job.

PILOT605E**GETMAIN REQUEST FOR WORKING STORAGE HAS FAILED, PROCESS TERMINATED.**

The program issued a request for storage which failed. Please increase the REGION size in your JCL and run the job again.

PILOT606E

FREEMAIN FOR GETMAINED STORAGE HAS FAILED, PROCESS TERMINATED.

The program issued a request to free storage it obtained earlier in the process, and this request has failed. This is probably a logic error which should not occur. Please contact technical support.

PILOT607E

OPEN OF FILE "SYSPRINT" HAS FAILED. PLEASE CHECK JCL ALLOCATION.

The program attempted to open the 'SYS-PRINT' file, and this request failed. The SYSPRINT DD statement is either missing, or has been misdefined. Please correct the JCL, and run the job again.

PILOT608E

OPEN OF FILE "V1M5HIST" FAILED. PLEASE CHECK JCL ALLOCATION.

The program attempt to open the 'V1M-5HIST' file, and this request failed. The V1M5HIST DD statement is either missing, or has been misdefined. Please correct the JCL, and run the job again.

PILOT609E

GETMAIN LENGTH ERROR, OR FAILED TO OBTAIN DIRECTORY BLOCK STORAGE.

The program attempted to store directory block information in a previously obtained storage area, and has run out of room in this storage area. This is probably a logic error in the program, or it may mean the input HISTORY PDS is being updated at the same time the CONVHIST program is being run. Please make sure access to the input HISTORY PDS is serialized, and run the job again. If the error persists, please contact technical support.

PILOT610E

ERROR OCCURRED DOING FIND MACRO RC=XXXX, AND REASON CODE = XXXX.

The program issued a FIND macro and received the above return code and reason code as a response. Check the FIND macro return code/reason codes in the DFSMS Macro Instructions For Datasets manual to see if there is a cause that can be corrected via the JCL. If not, please contact technical support.

PILOT611E

OPEN OF FILE "V1M7HIST" FAILED. PLEASE CHECK JCL ALLOCATION.

The program attempt to open the 'V1M7-HIST' file, and this request failed. The V1M7HIST DD statement is either

missing, or has been misdefined. Please correct the JCL, and run the job again.

PILOT612E

ERROR OCCURRED DOING STOW MACRO RC=XXXX, AND REASON CODE = XXXX.

The program performed a STOW macro, and received the displayed return and reason codes as an exception response. Please check the return/reason codes in the DFSMS Macro Instructions For Datasets manual to see if there is a correction that can be made to the JCL to fix the problem. If not, please contact technical support.

PILOT620E

AN UNEXPECTED ERROR HAS BEEN ENCOUNTERED. CALL TECHNICAL SUPPORT.

An error has occurred which was not designed to be handled by the program. Please contact technical support.

PILOT630E

SYNADF=unit,type,ddname,operation, error,ttr,accessmethod

An I/O error occurred reading the HISTORY file. The results of the SYNADF request is displayed. Correct the error and rerun the job.

PILOT631

DYNAMIC ALLOCATION ERROR REASON CODE-rrrr ERROR CODE-eeee

The dynamic allocation of an input or output data set failed. The SVC 99 reason and error codes received by module RDSMFDYN are displayed.

PILOT632

DYNAMIC CONCATENATION ERROR REASON CODE-rrrr ERROR CODE-eeee

The dynamic concatenation of a list of input data sets failed. The SVC 99 reason and error codes received by module RDSMFDYN are displayed.

PILOT633

DYNAMIC ALLOCATION WAS SUCCESSFUL

The dynamic allocation of an input or output data set was successful.

PILOT634

DYNAMIC CONCATENATION WAS SUCCESSFUL

The dynamic concatenation of a list of input data sets was successful.

User Abends

<u>Code</u>	<u>Module</u>	<u>Reason</u>		
U001				Sales Representative at Axios Products, Inc.
U002				
U003	RDSMFAUT	A dynamic allocation failed. Call for support	U201	RDSMFAM SYSUT1 open failed for VSAM.
U100	RDSMFAM MONPCAM	An invalid function was requested from another module. Contact Axios Products, Inc.	U202	RDSMFAM SYSUT2 open failed for VSAM.
U101	RDSMFAUT RDSMFDYN	An invalid function call was made. Contact Axios Products, Inc.	U300	RDSMFAM SYSUT1 GET macro failed. The data set could not be read.
U102	RDSMFXCP	The exception processor module was called with a bad function code. Call for support.	U400	RDSMFAM SYSUT2 PUT macro failed. The output record could not be written.
U103	ALL	Your trial has expired, or you are not running PILOT on an authorized CPU. Contact your	U500	RDSMFAUT A TESTAUTH macro instruction failed, the module is not authorized.
			U600	RDSMFHST A logic error occurred in the History routine. Contact Axios Products, Inc.

U700 READSMF This message is
 issued if you reply
 "U" to abend in
 response to message
 PILOT224E.

Table Error Return Codes

The following errors indicate that there is not enough virtual storage. All other table errors are internal errors which should be reported to Axios Products, Inc. technical support.

Return code 20 No more available storage
Return code 24 Initial storage GETMAIN
 error

Index

account.	3 , 9 , 13 , 15
action.	1
allocation..	7 , 12 , 13 , 18-21
cache.	17
capacity planning..	2
channel.	7
cics.	18
cpu.	8 , 15 , 16 , 21
cpu model.	15
dasd.	17
date.	9 , 10 , 13
dd.	3 , 10 , 11 , 16 , 19
ddname..	14 , 20
default.	1 , 3 , 5
dynamic allocation..	7 , 12 , 13 , 18 , 20 , 21
end.	1 , 9 , 10
exclude.	17 , 18
exit.	3 , 4 , 11 , 12
group.	4 , 8 , 12-16
history.	5 , 6 , 10 , 12 , 13 , 18-21
history option.	10
ics.	4 , 8 , 15 , 16
include.	17 , 18
interval.	8 , 16
ismf.	3 , 7 , 10
jcl.	11 , 17 , 19 , 20
jobname.	11
lotus..	7
mips..	15
model.	15 , 16
model generator.	16
opened.	4 , 13 , 16
output files..	16
parameters.	3 , 5 , 7 , 10
parmlib.	4 , 16
parms.	3

peaktime.	11
performance.	2 , 4 , 7 , 8 , 11 , 12 , 15 , 16
pgn.	4 , 8
pilot/cics.	18
pilot/smf.	7
print.	16
readsmf.	3 , 4 , 7 , 9 , 10 , 12 , 13 , 22
response.	5 , 19 , 20 , 22
rmf.	4 , 8 , 10 , 16 , 17
rmfctl.	13
select.	9
simbuild.	16
smf.	3 , 4 , 7 , 10 , 12 , 13
smfpc110.	17
smfpc30.	15
start.	9 , 10 , 14 , 15
statistics log.	3
syntax.	3 , 9-11 , 13-17
sysid.	17
sysin.	3
sysprint.	19
system.	2-4 , 7 , 10 , 12 , 16
sysut1.	3 , 7 , 13 , 21
sysut2.	5 , 7 , 21
time.	3 , 7 , 10 , 11 , 13 , 16 , 19
tso.	8 , 11 , 12
type.	4 , 8-10 , 17 , 20
unit.	17 , 20
user exit.	12
volser.	15
volume.	12 , 15
workload.	8 , 17